



- AC4 Impact Class
- Suitable for Heavy Domestic and Medium Commercial Use
- 25 Year Domestic Warranty
- Made in Europe
- Easy push down drop lock System
- 4V Bevel Edge
- Suitable for underfloor heating



Easy Push Down Drop Lock System

AC4 / 32



PACKAGING	8 PANELS
LENGTH	1383 MM
WIDTH	159 MM
THICKNESS	10 MM
COVERAGE AREA	1.76 M2

BEFORE YOU START

- Consult instructions for details on site conditions. Moisture content of cement subfloor must be $\leq 3\%$ (2.0% C.M.). Pump/ anhydrite screeds must be $\leq 0.3\%$ C.M. Wood subfloor moisture should be $10\% \pm 2\%$
- Install 0.2mm/500 gauge polythene on all concrete surfaces.
- Overlap joints by 200mm and seal with duck tape.
- Check that the subfloor is level and even before installation – max. 3mm differential over 1mt.
- Use a good quality flooring underlay for your floor. We recommend a maximum thickness of 3mm. Heavier underlays should have a minimum density of 53kg/m3.
- Not suitable for use in wet rooms.
- LEAVE BOXES UNOPENED IN ROOM FOR 48 HOURS PRIOR TO INSTALLATION.

DURING & AFTER INSTALLATION

- Select board direction e.g. towards light or longest room dimension. This floor has a click system.
- Install as a floating floor with for 12mm (minimum) expansion around perimeter and all fixed objects. Please note that the maximum running span for Metro Narrow Laminate flooring is 8metre in any direction. Expansion gap should be provided at all doorways.
- Follow installation instructions for first and second row.
- Stagger joints by min. 40cm thereafter.
- Select finishing profiles, skirting, pipe covers, doorway slips.
- Use felt pads and protective castors underneath furniture legs.
- Please use suitable cleaning products for aftercare.
- DO NOT USE STEAM CLEANERS ON METRO LAMINATE FLOORING

